



Electronic Faucets

EC-3107-LN



ChekPoint™



Electronic Sensor Faucet

TAG:

Architect/Engineering Specifications:

4" c/c deck mount electronic sensor faucet with polished chrome plated brass body, 3/8" NPT female outlet (less nozzle), AC/DC control module with internal flow control setting switches, temperature control mixing valve with integral check valves and 18" flexible stainless steel supply hoses with 3/8" compression connections. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9, NSF 372 and UL 1951. Meets ADA ANSI/ICC A117.1 requirements.

Job Name _____
 Model Specified _____ Quantity _____
 Variations Specified _____
 Date _____



Features & Benefits:

- 4" c/c deck mount faucet w/ polished chrome plated brass body
- 3/8" NPT female outlet accepts T&S rigid goosenecks
- Water resistant control module w/ internal flow control switches for adjusting auto time out & shut off delay settings
- Optional auto flush feature flows water for 30 seconds after every 12 inactive hours
- Optional metering mode
- Plug in AC transformer or (4) AA battery (DC) power options
- Mechanical temperature mixing valve with integral check valves
- 18" flexible stainless steel supply hoses with 3/8" compression connections
- Low battery LED indicator light
- Material: Polished chrome plated brass body and gooseneck

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 - Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)
- UL 1951

Warranty: Three Year (Limited)

Performance Data:

- Pressure: 20 - 125 psi [1.38 - 8.62 bar]
- Temperature: 40°F - 140°F [4.4°C - 60°C]
- Flow Rate: 5.8 GPM [22.0 L/min] @ 60 psi [4.14 bar]
- Water Consumption: @ 10 sec = .97 gal [3.66 L]
 @ 15 sec = 1.45 gal [5.49 L]



ADA Compliant



Optional Outlets (Series 2 / VR Series 7)

(Outlet Device &/or Final Configuration May Reduce Flow Rate)

GPM	Aerated	Non-Aerated (Laminar)	VR Aerated	VR Non-Aerated (VR Laminar)	T&S Rigid Goosenecks (D x K)
0.35	N/A	☐ B-0199-02-N035	N/A	☐ B-0199-07-N035	☐ 119X 2 5/8" x 5 1/4" Rigid Gooseneck
0.5	N/A	☐ B-0199-02-N05	N/A	☐ B-0199-07-N05	☐ 120X 5 1/2" x 5 1/4" Rigid Gooseneck
1.0	☐ B-0199-02-F10	N/A	☐ B-0199-07-F10	N/A	☐ 122X 5 1/2" x 6 1/2" Rigid Gooseneck
1.2	☐ B-0199-02-F12	N/A	☐ B-0199-07-F12	N/A	☐ 123X 5 1/2" x 7 1/2" Rigid Gooseneck
1.5	☐ B-0199-02-WS	N/A	☐ B-0199-07-WS	N/A	☐ 129X 8 1/2" x 5 7/16" Rigid Gooseneck
2.2	☐ B-0199-02	N/A	☐ B-0199-07	N/A	☐ 165X 4 1/16" x 5 13/16" Rigid Gooseneck



T&S BRASS AND BRONZE WORKS, INC.



• 2 Saddleback Cove • Travelers Rest, SC 29690
 Ph 800-476-4103 • Fax 864-834-3518
 • Simi Valley, CA • Ph 800-423-0150 • www.tsbrass.com

Date: 04/24/20