

Project		
AIA #	SIS #	
ltem #	Quantity	C.S.I. Section 114000



G-SERIES

3-Section Refrigerator Reach-In Self-Contained Solid Door(s)





Many models are ENERGY STAR® listed. Please refer to www.energystar.gov to view the most up-to-date product listing and performance data.







Intertek CERTIFIED TO ANSI/NSF 7

This unit is listed to the applicable UL, CSA and NSF Standards by an approved NRTL. Consult the factory or unit's data plate for approval information.

AVAILABLE CONFIGURATIONS

Half-Height Door Models	Hinging
G30000	Left/Right/Right
G30001	Left/Left/Right
G30002	Right/Right/Right
G30003	Left/Left/Left

Full-Height Door Models	Hinging
G30010	Left/Right/Right
G30011	Left/Left/Right
G30012	Right/Right/Right
G30013	Left/Left/Left

STANDARD PRODUCT FEATURES

- High Performance, Energy Efficient Refrigeration System
- Reliable Microprocessor Control With LED Temperature Display
- Evaporator Coil Outside Food Zone Provides More Usable Space
- Load-Sure Guard Prevents Problems From Improper Loading
- Durable All Metal Construction
- Stainless Steel Front & Doors, Anodized Aluminum Sides & Interior
- Full or Half Height Door Models with a Variety of Hinging Configurations
- Long Life EZ Clean Door Gaskets
- Three (3) Epoxy Coated Shelves Per Section (factory installed)
- Easy to Maintain Front Facing Condenser Coil
- 6" High Locking Casters
- Guaranteed for Life Door Handles & Hinges
- 3-Year Parts & Labor Warranty
- 2-Years Additional Compressor Parts Warranty

ACCESSORIES & OPTIONS (*field installed)

- Tray Slides for 18" x 26" Sheet Pans*
- Tray Slides for 12" x 20" Food Pans*
- Tray Slides for 14" x 18" Sheet Pans*
- Tray Slides for 18" x 26, 12" x 20" & 14" x 18" Pans*
- Additional Shelves*
- 6" High Legs*
- Lower Height Casters*
- Optional Remote Applications

Approved by _____ Date____ Approved by _____ Date____


^{*}Please refer to form number TR35872 for precise kit details. See back page for tray slide versatility chart.





MODELS

Half Height Door Models: G30000, G30001, G30002, G30003










3-Section Refrigerator Reach-In Self-Contained Solid Door(s)

MODELS
Full Height Door Models: G30010, G30011, G30012, G30013







3-Section Refrigerator Reach-In Self-Contained Solid Door(s)

MODELS

Half Height Door Models: G30000, G30001, G30002, G30003 Full Height Door Models: G30010, G30011, G30012, G30013

MODELS	G300				
DIMENSIONAL DATA					
Net Capacity cu. ft. ¹	69.15 (1958 l) 69.35 (1964 l)				
L x D x H - Overall in. ²	76 ⁵ / ₁₆ (193.8 cm) x 35 (88.8 cm) x 83 ⁷ / ₁₆ (211.9 cm)				
Depth - over body in.	32 [81.3 cm]				
Depth - door open 90° in.	57% (146.3 cm)				
Clear half-door W x H in.	211/8 (53.6 cm) x 271/2 (69.9 cm)				
Clear full-door W X H in.	21½ (53.6 cm) x 57½ (146.3 cm)				
No. Standard Shelves	9				
Shelf Area sq. ft. ³	51.9 (4.82 sq m)				
ELECTRICAL DATA					
Voltage Plug	115/60/1 NEMA 5-15P (attached)				
Feed wires with ground	3				
Full Load Amperes MDEC ⁴	8.4 3.38 KWH/Day				
REFRIGERATION DATA					
Refrigerant	R-450A				
Refrigerant Charge Amount	24 oz				
BTU/HR H.P. ⁵	4610 1/2 HP				
Required Clearance	12" Above				
SHIPPING DATA					
L x D x H Crated in.	91(231 cm) x 42 (107 cm) x 85(216 cm)				
Volume Crated cu. ft.	188 (5324 เ)				
Uncrated Crated Weight lbs.	610 (277 kg) 630 (286 kg)				

NOTES:

- 1. Net Capacity cu. ft. = Half Height Door | Full Height Door models.
- 2. Height shown when mounted on standard 6" high casters.
- $\ensuremath{\mathsf{3}}.$ Figure shown reflects the area of standard shelf compliment.
- 4. MDEC = Maximum Daily Energy Consumption
- 5. Based on a 90°F ambient and 20°F evaporator. For remote data please refer to spec sheet TR35837.

EQUIPMENT SPECIFICATIONS

CONSTRUCTION, HARDWARE, INSULATION

Cabinet exterior front, louver assembly and door(s) are constructed of 20 gauge stainless steel. Cabinet sides (including returns), interior and door liners are constructed of anodized aluminum. The exterior cabinet top, back and bottom are constructed of heavy gauge galvanized steel. A set of four (4) 6" high locking casters are included. Doors are equipped with a gasket protecting, raised metal door pan, cylinder locks, and guaranteed for life self-closing cam-lift hinges with a stay open feature at 120 degrees. Hinges include a concealed switch to automatically activate the interior LED lighting. Guaranteed for life, metal work flow door handles are mounted horizontally over recess in door which limits protrusion into aisle ways. Gasket profile and durable long life material simplify cleaning and increase overall gasket life. Anti-condensate heaters are located behind each door opening. Both the cabinet and door(s) are insulated with an average of 2" thick high density, non-CFC, 100% foamed in place polyurethane.

SELF-CONTAINED REFRIGERATION SYSTEM

A top mounted, self-contained, balanced refrigeration system using environmentally friendly, non-flammable R-450A refrigerant is conveniently located behind the one piece louver assembly. It features an easy to clean front facing condenser, thermostatic expansion valve metering device, air-cooled hermetic compressor, large, high humidity evaporator coil located outside the food zone and a top mounted non-electric condensate evaporator. A 9' cord and plug is provided. Standard operating temperature is 34 to 38°F.

CONTROL

The easy to use water resistant microprocessor control is supplied standard. It includes a 3-Digit LED Display, and a Fahrenheit or Celsius Temperature Scale Display Capability.

INTERIOR ARRANGEMENTS

Standard interior arrangements include three (3) epoxy coated steel wire shelves per section, mounted on shelf pins, installed at the factory. Shelves are full-width, and do not have any large gaps between them requiring the use of "bridge" or "junior shelves." Recommended load limit per shelf should not exceed 225 lbs.

DOMESTIC WARRANTY

Both a three year parts and labor warranty and an additional two year compressor parts warranty (for a total of five on selfcontained models) are provided standard.

	OPTIONAL ACCESSORY TRAY SLIDE VERSATILITY CHART							
TRAY SLIDE DRAWINGS								
TRAY SLIDE OFFERING	#1 (1) 18" x26" or (2) 14"x18"	#4 (Rod Type) (1) 18" x26"	Universal (1) 18" x26" or (2) 14"x18" or (2) 12"x20"	#1 EZ-Change (1) 18" x26" or (2) 14"x18"	Universal EZ-Change [1] 18" x26" or [2] 14"x18" or [2] 12"x20"	HD Universal EZ-Change [1] 18" x26" or [2] 14"x18" or [2] 12"x20"		
SPACING CAPACITY DOOR SIZE	2" 28 Pairs Full Door & 13 Half 3" 19 Pairs Full Door & 09 Half 4" 14 Pairs Full Door & 07 Half 5" 11 Pairs Full Door & 05 Half	(2 Pair) 1 1/2" 18 Pairs Half Door	4" 14 Pairs Full Door & 06 Half ¹ 4" 14 Pairs Full Door & 07 Half ² 5" 11 Pairs Full Door & 05 Half 6" 09 Pairs Full Door & 04 Half	2" 26 Pairs Full Door & 12 Half 4" 13 Pairs Full Door & 06 Half	2 1/4" 22 Pairs Full Door & 11 Half 4 1/2" 11 Pairs Full Door & 05 Half	4 1/2" 11 Pairs Full Door & 05 Half 9" 05 Pairs Full Door & 02 Half		

- Upper Half Height Door1
- Lower Half Height Door²