Model Specified: CSI Section 11400

## 26" Deep Reach-In Refrigerator Models/ Self-Contained



Model Shown One Section

(shown with optional casters)

## One & Two Section Models, 26" Deep



Stainless Exterior & Interior

1-Section Full Length Door Model
2-Section Full Length Door Model
1-Section Half Length Door Model
2-Section Half Length Door Model
RHT126WUT-FHS
RHT126WUT-HHS



Stainless Exterior, Anodized Aluminum Interior

1-Section Full Length Door Model
2-Section Full Length Door Model
1-Section Half Length Door Model
2-Section Half Length Door Model
AHT126WUT-FHS
AHT126WUT-HHS

The 26" deep reach-in refrigerator models are all designed to offer maximum interior storage capacity within a slightly shallower footprint. Each is supplied standard with such high quality features as balanced refrigeration systems, microprocessor controls, and stainless steel exteriors. Additionally, they offer the widest range of optional accessories to choose from, and can be specified for use with many different applications, including: Foodservice, Correctional, nstitutional, Export, etc.

## **Standard Product Features**

- · Traulsen's Smart Control with LED Display
- StayClear™ Condenser
- R-Series: Stainless Steel Exterior & Interior
- · A-Series: Stainless Steel Exterior/Anodized Aluminum Interior
- · Balanced, Self-Contained Refrigeration System Using R-450A
- · Rear Biased Return Air Duct
- Full or Half Length Stainless Steel Doors With Locks
- Self-Closing Doors With Stay Open Feature At 120°F
- Guaranteed For Life Cam-Lift Hinges
- · Guaranteed For Life Horizontal Work Flow Door Handle
- Standard Door Hinging: 126W = Right, 226W = Left/Right (other hingings available)
- Automatically Activated LED Lights
- Stainless Steel Breaker Caps
- Three Adjustable Wire Shelves Per Section, Supported On Shelf Pins (installed at the factory)
- Automatic Non-Electric Condensate Evaporator
- Magnetic Snap-In EZ-Clean Door Gasket(s)
- Gasket-Protecting Metal Door Liner
- · Thermostatic Expansion Valve Metering Device
- Stainless Steel One-Piece Louver Assembly
- 9' Cord & Plug Attached
- Set of Four (4) 6" High Adjustable Stainless Steel Legs
- · Three Year Parts And Labor Warranty
- Five Year Compressor Warranty

# **Options & Accessories**

- Stainless Steel Finished Back With Rear Louvers
- Re-Hinging Feature For Door(s)
- · Additional Wire Shelves
- EZ-Open Foot Pedal (full height doors only)
- Locking Hasps (padlocks supplied by others)
- Export 220/50/1 Voltage
- Stainless Steel Shelves
- Kool Klad Exterior Laminate Decor
- · Set of Four (4) 6" High Casters In Lieu of Legs
- Set of Four (4) 4-5/8" High Casters In Lieu of Legs
- · 4-1/2" High Stainless Steel Base In Lieu of Legs
- 6" High Stainless Steel Kickplate (for use with standard legs)
- Prison/Correctional Facilities Options
- Remote Applications (see form TR35837 for more details)3
- Remote For Use With 20°F Glycol System
- Wine Holding Applications (operates at 53-57°F and includes 8 wine bottle shelves per section)
- Clear Glass Door(s) In Place Of One Or More Solid Door(s)





Listed by Underwriters Laboratories Inc., to U.S. and Canadian safety standards and Listed by NSF International.





Project Quantity Item #

Model Specified: CSI Section 11400

## **Specifications**

#### Construction, Hardware and Insulation

Cabinet exterior front, one piece sides, louver assembly and doors are constructed of 20 gauge stainless steel with #4 finish. Cabinet interior and door liners are constructed of stainless steel (anodized aluminum in the A-Series). The exterior cabinet top, back and bottom are constructed of heavy gauge galvanized steel. A set of four (4) adjustable 6" high stainless steel legs are included.

Doors are equipped with a gasket protecting metal door pan, removable plug cylinder locks and guaranteed for life cam-lift, gravity action, self-closing metal, glide hinges with stay open feature at 120°F. Hinges include a concealed switch to automatically activate the interior LED lighting. Guaranteed for life, work flow door handles are mounted horizontally over recess in door which limits protrusion from door face into aisleways. Doors have seamless, polished metal corners

Gasket profile and Santoprene\* material simplify cleaning and increase overall gasket life. Anti-condensate heaters are located behind each door opening.

Both the cabinet and door(s) are insulated with an average of 2" thick high density, non-CFC, foamed in place polyurethane.

DIMENSIONAL DATA	R/AHT126WUT	R/AHT226WUT
Net capacity cu. ft.	19.1 (541 cu l)	40.8 (1156 cu l)
Length - overall in.	29% (75.9 cm)	58 (147.3 cm)
Depth - overall in.	29 (73.6 cm)	29 (73.6 cm)
Depth - less handle in.	27¾ (69.4 cm)	27¾ (69.4 cm)
Depth - over body in.	26 (66.0 cm)	26 (66.0 cm)
Depth - door open 90° in.	51 <sup>11</sup> / <sub>16</sub> (131.3 cm)	51 <sup>11</sup> / <sub>16</sub> (131.3 cm)
Clear door width in.	21½ (54.6 cm)	21½ (54.6 cm)
Clear half-door height in.	27½ (69.9 cm)	27½ (69.9 cm)
Clear full-door height in.	57% (146.3 cm)	57% (146.3 cm)
Height - overall on 6" legs⁴	83¼ (211.5 cm)	83¼ (211.5 cm)
RHT Net Wt. lbs.1	345 (156 kg)	550 (249 kg)
AHT Net Wt. lbs.1	305 (138 kg)	480 (218 kg)
No. Standard Shelves	3	6
Shelf area sq. ft.2	14.6 (1.35 sq m)	29.2 (2.71 sq m)
ELECTRICAL DATA		
Voltage	115/60/1	115/60/1
Feed wires with Ground	3	3
Full load amperes	8.0	8.5
REFRIGERATION DATA		
Refrigerant	R-450A	R-450A
Refrigerant Charge Amount	14 oz	27 oz
BTU/HR H.P <sup>3</sup>	2220 (1/3 hp)	2220 (1/3 hp

#### NOTES

NOTE: Figures in parentheses reflect metric equivalents

Part No. TR35757 (REV. 01-21-19)

- 1= For shipping weights and dimensions please refer to spec sheet form TR35875
- 2= Area of standard shelf compliment only, does not include storage area of additional shelves or available on cabinet bottom.
- 3= Based on a 90°F ambient and 20°F evaporator. For information on remote models, please refer to form TR35837.
- 4= 12" Top clearance preferred for optimum performance and service access.

# Equipped With One NEMA 5-15 P Plug NOTE: Full load amps and plug style may vary depending on electrical options chosen and condensing unit employed.

### **Refrigeration System**

A top mounted, self-contained, balanced refrigeration system using environmentally friendly, non-flammable R-450A refrigerant is conveniently located behind the one piece louver assembly. It features a finless StayClear™ condenser, thermostatic expansion valve, air-cooled hermetic compressor, large, high humidity evaporator coil located outside the food zone and a top mounted non-electric condensate evaporator. Biased return air duct protects against introduction of warm kitchen air, promoting even temperature maintenance and efficient operation. A 9' cord and plug is provided. Standard operating temperature is 34 to 38°F.

#### Controller


Traulsen's Smart Control features advanced control algorithms and sophisticated diagnostic capabilities. Smart sensors will adapt the operation of the refrigeration system to a variety of environments and usage patterns. The Smart Control offers a complete set of visual alarms designed to alert the user to critical events. In the event of an alarm, a dedicated Alarm LED will illuminate, informing the user of the critical event and describing the event in the large, easy to read full text display.


#### Interior


Standard interior arrangements include three (3) coated wire shelves per section, mounted on shelf pins. Shelves are full-width, and do not have any large gaps between them requiring the use of "bridge" or "junior shelves". Recommended load limit per shelf should not exceed 225 lbs. Both standard and optional interior arrangements are installed at the factory.


#### Warranties

Both a three year parts and labor warranty and a five year compressor warranty (self-contained models only) are provided standard.









NOTE: When ordering please specify: Voltage, Hinging, Door Size, Options and any additional warranties. Continued product development may necessitate specification changes without notice.

TRAULSEN
4401 BLUE MOUND RD.
PHONE 1 (800) 825-8220
Website: www.traulsen.com

FT. WORTH, TX 76106 FAX-MKTG. 1 (817) 624-4302

