



4184 E. Conant st., Long Beach, CA 90808
 Tel. 800-500-3519 Fax. 310-900-1066
www.turboairinc.com

Project :

Model # :

Item # :

Qty :

Available W/H :

Approval :

60" Wide Heavy Duty Restaurant Ranges - Combination



TARG-4B36G



TARG-24G6B

≡ FEATURES & BENEFITS ≡

- Heavy gauge welded frame construction
- Stainless steel front, sides, back riser lift-off high shelf
- Individual pilot for each lift off top open burner at 32,000 btu/hr
- 6" stainless steel adjustable legs (casters available as an option)
- 12" x 12" sectioned heavy duty cast iron grates
- Full size pull out crumb tray
- Wrap around full stainless steel oven interior / 26.3" depth standard
- Fully adjustable oven thermostat providing temperatures from 250-550°F degrees
- Pull out stainless steel door for easy cleaning
- Thermostat controlled griddle
- 1 stainless steel oven rack standard (additional racks optional)
- CSA certified for safety / sanitation for USA and Canada



Model	Oven	Weight (lbs.)	Width (inches)	Total BTUs	Configuration
TARG-2B48G / 48G2B	2	1095	60	215K	2 Bunner / 48" Griddle Combo (NAT)
TARG-4B36G / 36G4B	2	1025	60	257K	4 Bunner / 36" Griddle Combo (NAT)
TARG-6B24G / 24G6B	2	995	60	299K	6 Bunner / 24" Griddle Combo (NAT)
TARG-8B12G / 12G8B	2	980	60	348K	8 Burner / 12" Griddle Combo (NAT)
TARG-2B48G-LP / 48G2B-LP	2	1095	60	209K	2 Burner / 48" Griddle Combo (LPG)
TARG-4B36G-LP / 36G4B-LP	2	1025	60	251K	4 Burner / 36" Griddle Combo (LPG)
TARG-6B24G-LP / 24G6B-LP	2	995	60	293K	6 Burner / 24" Griddle Combo (LPG)
TARG-8B12G-LP / 12G8B-LP	2	980	60	342K	8 Burner / 12" Griddle Combo (LPG)

60" Wide Heavy Duty Restaurant Ranges - Combination


DATA	TARG-2B48G / 48G2B	TARG-4B36G / 36G4B	TARG-6B24G / 24G6B	TARG-8B12G / 12G8B
Gas Type	NAT	NAT	NAT	NAT
Gas Connection	3/4" x 2	3/4" x 2	3/4" x 2	3/4" x 2
Regulator	3/4"	3/4"	3/4"	3/4"
Gas Pressure	5 W.C"	5 W.C"	5 W.C"	5 W.C"
BTU	215,000	257,000	299,000	348,000
DIMENSIONAL DATA				
Ext. Length Overall (inch)	60 (1524mm)	60 (1524mm)	60 (1524mm)	60 (1524mm)
Ext. Depth Overall (inch)	31 7/8 (810mm) + manifold	31 7/8 (810mm) + manifold	31 7/8 (810mm) + manifold	31 7/8 (810mm) + manifold
Ext. Height Overall (inch)	56 1/2 (1436mm)	56 1/2 (1436mm)	56 1/2 (1436mm)	56 1/2 (1436mm)
OVEN DIMENSION (Interior)				
Number of Oven	2	2	2	2
Length (inch)	26 3/8 (670mm)	26 3/8 (670mm)	26 3/8 (670mm)	26 3/8 (670mm)
Depth (inch)	26 1/4 (669mm)	26 1/4 (669mm)	26 1/4 (669mm)	26 1/4 (669mm)
Height (inch)	13 5/8 (345mm)	13 5/8 (345mm)	13 5/8 (345mm)	13 5/8 (345mm)
Weight (lbs.)	1095	1025	995	980
DATA				
Gas Type	LPG	LPG	LPG	LPG
Gas Connection	3/4" x 2	3/4" x 2	3/4" x 2	3/4" x 2
Regulator	3/4"	3/4"	3/4"	3/4"
Gas Pressure	10 W.C"	10 W.C"	10 W.C"	10 W.C"
BTU	209,000	251,000	293,000	342,000
DIMENSIONAL DATA				
Ext. Length Overall (inch)	60 (1524mm)	60 (1524mm)	60 (1524mm)	60 (1524mm)
Ext. Depth Overall (inch)	31 7/8 (810mm) + manifold	31 7/8 (810mm) + manifold	31 7/8 (810mm) + manifold	31 7/8 (810mm) + manifold
Ext. Height Overall (inch)	56 1/2 (1436mm)	56 1/2 (1436mm)	56 1/2 (1436mm)	56 1/2 (1436mm)
OVEN DIMENSION (Interior)				
Number of Oven	2	2	2	2
Length (inch)	26 3/8 (670mm)	26 3/8 (670mm)	26 3/8 (670mm)	26 3/8 (670mm)
Depth (inch)	26 1/4 (669mm)	26 1/4 (669mm)	26 1/4 (669mm)	26 1/4 (669mm)
Height (inch)	13 5/8 (345mm)	13 5/8 (345mm)	13 5/8 (345mm)	13 5/8 (345mm)
Weight (lbs.)	1095	1025	995	980

Design and specifications subject to change without notice.
Actual shipping weight may differ due to extra packing materials for product protection.

OPTIONAL ACCESSORIES :

- Casters (Set of 4)
- Stainless steel oven racks

WARRANTY : 1 Year Labor and Parts Warranty



Ver.20200528



- Turbo Air : 800-627-0032
- GK : 800-500-3519
- Warranty : 800-381-7770
- AC : 888-900-1002