

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Pro	iant	•
110		

Model # : Item # :

Qty :

Available W/H :

Approval :

# Direct Cooling Type Deli Cases

Bakery & Deli Cases High Profile

### Patented Self-Cleaning Condenser









## \_\_\_\_ FEATURES & BENEFITS \_\_\_\_

#### Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

#### Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

#### Attractive, elegant, glass sided Euro design

Curved tempered front glass and minimal frame provide full product visibility to optimize display effects. Its elegant contemporary euro design will not only enhance any store atmosphere but also will keep product presentation at its best and most beautiful.

#### High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

- Low-E coated double pane glass is tempered for safety
- Easy access control panel
- Sliding rear doors for product loading & unloading
- Heavy duty, white PE coated wire shelves
- Cantilever wired shelves adjustable up and down, tilted
- Stainless steel floor and airflow grille
- Rear access to compressor compartment for quick and easy service
- Refrigerated deli case holds avg. 33°F ~ 41°F for fresher products

TCDD-96H-W(B)-N	33.2	4	3/4	7.8	957	961/2 x 30 x 501/8
Model	CU./FT.	# of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D x H (inches)
Refrigerant SANITATION CUIS COURT WARRINGT						

# Direct Cooling Type Deli Cases

## Model : TCDD-96H-W(B)-N

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	(i) NEMA 5-15P			
Full Load Amperes	7.8			
Compressor HP	3/4			
Refrigerant	R-290			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	33.2			
Ext. Length Overall (in.)	961/2 (2451mm)			
Ext. Depth Overall (in.)	30 (762mm)			
Ext. Height Overall (in.)	501/8 (1273mm)			
Int. Length Overall (in.)	931/4 (2370mm)			
Int. Depth Overall (in.)	24 (610mm)			
Int. Height Overall (in.)	235/8 (599mm)			
Shelf Size (in.)	461/8 x 153/4			
	461/8 x 173/4			
# of Shelves	4			
Power Cord Length (in.)	591/8			
Net Weight (lbs.)	802			
Gross Weight (lbs.)	957			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

### WARRANTY: 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

#### STANDARD FEATURES


- Anti-corrosion coated evaporator
- · Self-contained system, no plumbing required
- Safety shielded LED interior lighting
- Solar powered digital thermometer
- Digital electronic thermostat with defrost control

White and black colors come standard

- Recommended operating conditions

TCDD models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet. Air curtain models will run most efficiently when completely loaded with product.

(GERMAN)



SIDE VIEW

Ver 20190412



- **Turbo Air** : 800-627-0032 **GK** : 800-500-3519
- **Warranty** : 800-381-7770 **AC** : 888-900-1002



KNIFE

