

Sandwich/Salad Prep Table

- Stainless steel interior and exterior, Galvanized sheet back.
 - Refrigeration system keeps food at safe temperature between 33°F and 41°F (0.5 °C to 5°C).
 - Self-Closing doors with 90 degree stay-open feature.
 - Cutting boards and pans available.
 - Shelves: Adjustable heavy-duty epoxy coated shelves.
 - Option of different handles .
- Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - Pre installed heavy-duty casters with brakes.
 - Evaporation fan stop working when door is open, energy saving.
 - EC fan motor, lower energy consumption, less noise, higher efficiency.



MODEL	DOORS	SHELVES	DIMENSION(WxDxH) inches mm	CAPACITY cu.ft. liters	HP	AMPS	VOLTAGE	PLUG TYPE
VSP29	1	1	29*30*42 5/8 732*762*1082	7.6 215	1/5	1.7	115/60/1	5-15P
VSP48	2	2	48 1/4*30*42 5/8 1225*762*1082	13.8 390	1/5	1.7	115/60/1	5-15P
VSP60	2	2	60 1/4*30*42 5/8 1530*762*1082	17.8 505	1/4	2.1	115/60/1	5-15P
VSP72	3	3	72 11/16*30*42 5/8 1846*762*1082	21.2 601	1/4	2.1	115/60/1	5-15P

Mega top Sandwich/Salad Prep Table

- Stainless steel interior and exterior, Galvanized sheet back.
 - Refrigeration system keeps food at safe temperature between 33°F and 41°F (0.5 °C to 5°C).
 - Self-Closing doors with 90 degree stay-open feature.
 - Cutting boards and pans available.
 - Shelves: Adjustable heavy-duty epoxy coated shelves.
 - Option of different handles .
- Electronic control system makes it easy to adjust temperature set point and defrost frequency.
 - Pre installed heavy-duty casters with brakes.
 - Evaporation fan stop working when door is open, energy saving.
 - EC fan motor, lower energy consumption, less noise, higher efficiency.



MODEL	DOORS	SHELVES	DIMENSION(WxDxH) inches mm	CAPACITY cu.ft. liters	HP	AMPS	VOLTAGE	PLUG TYPE
VSP29(M)	1	1	29*30*42 5/8 732*762*1082	7.6 215	1/5	1.7	115/60/1	5-15P
VSP48(M)	2	2	48 1/4*30*42 5/8 1225*762*1082	13.8 390	1/5	1.7	115/60/1	5-15P
VSP60(M)	2	2	60 1/4*30*42 5/8 1530*762*1082	17.8 505	1/4	2.1	115/60/1	5-15P
VSP72(M)	3	3	72 11/16*30*42 5/8 1846*762*1082	21.2 601	1/4	2.1	115/60/1	5-15P