

| PROJECT: | | |
|----------|-------|------|
| ITEM # | | QTY: |
| MODEL # | | |
| AIA # | SIS # | |

EXTRA WIDE GLASS DOOR REACH-IN FREEZER

FSA-3D-S1-EW-G-HC



EXCLUSIVE WARRANTY

- **6 Year Parts & Labor Warranty**
- 7 Year Compressor Warranty
- Exclusive 2 Year Warranty On Magnetic Door Gaskets
- Lifetime Warranty On Handles & Hinges (parts only)



Optional: Ultra Glass Door











CABINET CONSTRUCTION

- · Stainless Steel Exterior
- **Aluminum Interior**
- Stay-Open Door Feature For Easy Product Loading
- · Glass Door
- · LED On/Off Selection Within Controller
- · Heavy-Duty Cylinder Locks
- One Piece, Snap-In Magnetic Door Gaskets
- Low Profile Vertical Door Handles
- Hinged Front Shroud
- · Energy Saving Thermal Breaker
- · Stainless Steel Breaker Caps
- · 9 Silver Freeze Wire Shelves
- 6" High Adjustable Stainless Steel Legs
- · 8' Cord And Plug (see electrical data for details)

FEATURES

- · Full Electronic Control With Touchpoint Interface
- · Expansion Valve Technology
- · Manager's Lockout Feature
- Anti-Condensate Perimeter Heater
- Variable Speed Compressor Technology

REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All **Environmental Concerns**
- · Hot Gas Condensate Evaporator
- Adaptive Defrost For Reduced Energy Consumption And More **Consistent Product Temperatures**
- · Epoxy Coated Evaporator Coil, Located Out Of The Food Zone
- · Freezer Capable Of Maintaining Product Temperature -10°F



Please Verify Qualifying Units By Visiting: www.energystar.gov/cfs

OPTIONS & ACCESSORIES

- Secure-Temp™ Technology
- · Stainless Steel Case Back
- · Stainless Steel Kick Plate
- Door Swing Orientation (at time of order) · Additional Shelves
- · Heat Shield (left, right)
- Tray Slides (type A & A/C)
- · 3", 6" Casters Or 6" Seismic Legs
- · Ultra Glass Door (as shown above)
- FlexTemp Models Maintain Between 0°F And 20°F

 Remote Models* (6" legs only) (refrigerant must be specified at time of order, see note)


3779 Champion Blvd, Winston-Salem, NC 27105

ph: (888) 845-9800 | fax: (800) 253-5168

Rev. 9/1/23 Printed in U.S.A.

APPROVAL: __ DATE: ___





We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

12" Top and 3" rear clearance is required

| CHARACTERISTICS | | ELECTRICAL DATA | | SHIPPING DETAILS | |
|------------------------------|---------------|---------------------------------|------------|--|---------|
| Net Capacity (cubic ft.) | 74.16 | Cabinet Voltage** | 115/60/1 | Height | 89" |
| Width, Overall (in.) | 85 1/2" | Total Amperes | 13.9 | Width | 109" |
| Depth, Overall (with handle) | 33 3/8" | NEMA Plug (8' cord) | 5-20P | Depth | 45" |
| Height Overall (6" legs) | 84 1/8" | REFRIGERATION DATA | | Crated Weight | 898 lbs |
| Depth, Door Open 90° | 58 3/4" | Condensing Unit Size, HP | (2) 3/4 | *NOTE: Remote units are field wired and comes with 6" legs. Refrigerant must be specified at | |
| Door Openings (in.) | 23" x 54 5/8" | Refrigerant | R-290 | | |
| No. Of Doors/Shelves | 3/9 | Capacity (BTU/HR) (100°F/-20°F) | 4900 | | |
| | | Heat Rejection (BTU/HR) | 7350 | time of order. | |
| | | Charge (lbs/grams) | 0.2866/130 | | |

^{**} NOTE: This unit utilizes variable speed compressor technology. The compressor can experience nuisance tripping on Class A GFCI outlets which have a trip limit of 4 mA to 6 mA. To avoid this issue in a location that requires GFCI circuit protection, Victory recommends using a HUBBELL Model Number GFRST83W 20A Heavy Duty Hospital Grade Self-Test GFCI Receptacle.

3779 Champion Blvd, Winston-Salem, NC 27105 | ph: (888) 845-9800 | fax: (800) 253-5168

Rev. 9/1/23 Printed in U.S.A.

