

**EXTRA HIGH ROLL-IN  
WARMING CABINET**

**Full Door**

HIS-1D-1-XH      HISA-1D-1-XH  
HIS-2D-1-XH      HISA-2D-1-XH

- 3 Year Parts & Labor Warranty Plus an Additional  
2 Year Compressor Warranty  
- Exclusive 2 Year Warranty on Santoprene Door Gaskets

# VICTORY

## ULTRASPEC™

### STANDARD FEATURES

- V-TEMP™ Electronic Control System
- Adjustable Electronic Temp Control from 80°F to 180°F
- Built-in, Adjustable Humidity Control Vent
- Safety Shielded Strip Type Heating Elements
- Externally Mounted Blower Maintains Even Temperatures
- Stainless Steel Doorjamb(s)
- Foamed-in-Place Polyurethane Insulation
- Heavy Duty Cylinder Locks
- Self-Closing Doors with 120° Hold Open Feature
- Cam-Lift Hinges, Guaranteed for Life
- Ergonomically Correct Door Handles, Guaranteed for Life
- Adjustable Door Wiper Gasket(s)
- Stainless Steel Floor
- Proximity Door Switch Activates Interior Lighting
- One Piece, Snap-In Magnetic Door Gasket(s)
- Stainless Steel Interior Door Liner
- Removable Ramp(s)
- Accepts Mobile Storage Racks up to 27" W x 29" D x 72" H



HIS-2D-1

### OPTIONS & ACCESSORIES

- Stainless Steel Case Back & Shroud
- Correctional Facilities Options
- Exterior Laminate Décor
- Optional Voltages (single section only)
- Cord and Plug



## CABINET CONSTRUCTION

The cabinet front and doors are constructed of heavy gauge, polished stainless steel to maintain an attractive appearance after years of heavy use. Polyurethane foam insulation throughout ensures the ultimate in energy efficiency.

## DOOR CONSTRUCTION

The doors are heavy gauge, polished stainless steel with a stainless steel interior liner. Each door is provided with a cylinder lock and ergonomically correct vertical handle. The door hinges are self-closing and have a hold open feature at 120° which facilitates product loading. Proximity switches energize the recessed interior incandescent lighting when the door is opened.

## HEATING SYSTEM

The safety shielded, "strip type" heaters located at the bottom of the cabinet interior are precisely controlled by the V-TEMP™ electronic control with a temperature range from 80°F to 180°F. An externally mounted blower system ensures even temperatures throughout the cabinet interior. A built-in, adjustable humidity control vent allows the operator to maintain a moist or drier environment.

## INTERIOR STORAGE ARRANGEMENTS

Each door opening accepts a mobile storage rack measuring up to:

27" W x 29" D x 72" H.

Optional shelf pilasters and wire shelves are available.

## V-TEMP™ CONTROL SYSTEM

The easy to use V-TEMP™ Control is provided standard with a two year parts and labor warranty. This durable, water resistant microprocessor monitors and controls the entire temperature maintenance process. It includes an ON/OFF switch located on the control face, interior light switch, LED temperature indicator in °C or °F, a HI/LO audio/visual temperature alarm, and a door ajar alarm. The control has set point memory. Upon start up, the unit will warm up to the last temperature set point. A manager's "lock-out" feature is provided to safeguard pre-determined control settings.

CHARACTERISTICS	1 SECTION	2 SECTION
Width, Overall (in.)	36 1/2"	68 7/8"
Depth, Overall (inc. Handles)	36 1/2"	36 1/2"
Depth, Door(s) Open 90°	65 1/2"	65 1/2"
Height Overall (in.)	89 7/8"	89 7/8"
Capacity Net (cu ft)	33.6	72.6
Clear Full Door Height	72 5/8"	72 5/8"
No. Full Doors	1F	2F

## ELECTRICAL DATA

Cabinet Voltage	208-240/60/1	208-240/60/1
Heater Watts Per Section	1500	1500
Total Wattage (heaters & fan @ 240)	1500	3000
Feed Wires	2	2
NEMA Plug	6-20P	6-20P
Total Amperes	6.3	13

**NOTE:** Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

CRATED DIMENSIONS	HT.	WIDTH	DEPTH	FT <sup>3</sup>	LBS
One Section	93 1/2"	42	43	97.72	385
Two Section	93 1/2"	77	43	179.15	580

