

**BOTTOM MOUNT REFRIGERATED
& FREEZER DISPLAY**

LSR49-1-G-L
LSF49-1-G-L

- Equipped with Secure-Temp 1.0™ Technology™
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty

VICTORY ULTRASPEC™

FEATURING: **SecureTemp**
1.0

Secure-Temp 1.0™ is the industry's first and only full service temperature monitoring solution for your kitchen. Secure-Temp 1.0™ is standard on all Victory models and is HACCP compliant & meets NAFEM's data protocol.

There are NO software or monthly monitoring fees.
Optional add on kits are available for additional units.

STANDARD FEATURES

- Secure-Temp 1.0™ Technology
- Full Electronic Control
- Food Safety Lock
- LED Lighting
- Expansion Valve Technology
- Santoprene Door Gaskets
- Stainless Steel Breaker Strips
- High Performance, Balanced, Bottom-Mounted Refrigeration
- Anti-Corrosion Coated Evaporator Coil
- Stainless Steel Interior/Exterior
- Environmentally Safe R134a Refrigerant For Refrigerators
- Environmentally Safe R404 Refrigerant For Freezers
- Min. 2.5" Foamed-in-Place Polyurethane Insulation
- Self-Closing Door(s) with 120° Hold Open Feature
- One Piece, Snap-In Magnetic Door Gasket(s)
- Heated Pressure Relief Vent
- Five (5) Chrome Plated Shelves Per Door Section
- Accommodates 18" x 26" or 12" x 20" pans
- Adjustable Leveling Legs
- Cam-Lift Hinges, Guaranteed for Life
- 10' Cord and Plug (see electrical data for details)



LSR49-1-G-L

OPTIONS & ACCESSORIES

- Change Door Swing
- Stainless Steel Finished Back
- 4" Overall Height Casters (Set of 4)
- Extra Shelves or Stainless Steel Shelves
- 220/50Hz, 220/60 Hz Voltages
- Remote Models Available



3779 Champion Blvd—Winston-Salem, NC 27105

PH: (888) 845-9800 - Fax: (800) 253-5168

sales@victoryrefrigeration.com www.victoryrefrigeration.com

LSR/LSF CABINET CONSTRUCTION

The cabinet front, grills and sides are constructed of polished stainless steel. The inside walls and bottom are in anodized aluminum. A minimum of 2.5" polyurethane foam insulation throughout (3.5" on the bottom) ensures energy efficiency. The front grill is snap-on /snap-off allowing easy access for cleaning the condenser,

LSR/LSF ELECTROIC CONTROL

Electronic thermostat with manual defrost button provides a digital display of cabinet temperatures, which includes status indicators and key pad for necessary temperature adjustments.

LSR/LSF ELECTRONIC CONTROL WITH FOOD SAFETY LOCK

Our exclusive Electronic Control with Food Safety Lock will lock the unit automatically when the power goes out. When the power is restored, if the power has been out for over "X" minutes, the door will stay locked. The factory preset is 120 minutes. If the temperature has been over "Y" temperature value for "Z" minutes the door will lock. The factory preset value for these parameters are 41° and 90 minutes for Refrigerators, and 32° and 60 minutes for Freezers. "X", "Y" and "Z" are programmable values. Additional standard features on the easy to use Electronic Control include **SUPERCOOL Mode**, **Energy Saving Mode**, and multiple audible and visual alarms (minimum temperature, maximum temperature, door ajar, probe failure, clean con-denser and compressor protection). The three most recent alarms are stored in memory. SUPERCOOL Mode runs the compressor constantly for a pre-determined amount of time or until a lower set-point has been reached. Energy Saving Mode activates automatically when there are no door openings for a pre-determined period of time.

LSR/LSF REFRIGERATION SYSTEM

Self contained bottom mount refrigeration system. Expansion valve refrigerant control on freezer

Provides quick temperature pull down and reduces compressor run time—meaning reduced energy consumption. Includes automatic condensate disposal. Refrigerators utilize ozone friendly R134a refrigerant. Freezers utilize ozone friendly R404a refrigerant and its defrost system is fully automatic, time initiated and temperature terminated operation.

LSR/LSF INTERIOR STORAGE ARRANGEMENTS

Each cabinet sections provided with five (5) chrome plated shelves. The shelves are adjustable in one inch increments.

Freezer product temperatures from -10°F to -15°F.
Refrigerator product temperatures from 36°F to 38°F.

| CHARACTERISTICS | REFRIGERATOR | FREEZER |
|-------------------------------|--------------|---------|
| DIMENSIONAL DATA | | |
| Width, Overall (in.) | 52" | 52" |
| Depth, Overall (inc. Handles) | 33 5/8" | 33 5/8" |
| Depth, Door(s) Open 90° | 55 7/8" | 55 7/8" |
| Height Overall (in.) | 78" | 78" |
| Capacity Net (cu ft) | 49 | 49 |
| No. Full Doors | 2 | 2 |
| No. of Shelves | 5 | 5 |

| ELECTRICAL DATA | | |
|-----------------|----------|----------|
| Cabinet Voltage | 115/60/1 | 115/60/1 |
| Total Amperes | 8.8 | 11.9 |

NOTE: Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

| REFRIGERATION DATA | | |
|----------------------|--------|--------|
| Condensing Unit Size | 1/3 HP | 3/4 HP |
| Refrigerant | R-134A | R-404A |

| CRATED WEIGHT | | |
|--------------------|--------|--------|
| ONE SECTION | 608LBS | 651LBS |

* Remote units use R-404A refrigerant standard and come with 6" legs

