



## Top-Mount Fabricator Well

- Designed for top-mount installation and requires hard wiring
- High-density glass fiber insulation allows use of 1000W elements
- Zero clearance for flexibility in installation
- Available for 120V, 208-240V power
- Beveled edge for easy cleaning
- Thermostatic control
- 4-foot flexible control cable
- Hard-wired input power connections
- Recommend using up to 4" (10.2 cm) deep pans – full and fractional sizes



ITEM #	OVERALL DIMENSIONS IN (CM)	WATTS	VOLTAGE	AMPS
36368	15 x 23 (38.1 x 58.4)	1000	120	8.3
36369	15 x 23 (38.1 x 58.4)	750-1000	208-240	3.6-4.2

\*With 3/8" (2.2 cm) corner radius    Note: Modular Drop-Ins cannot be canceled or returned

## Bottom-Mount Fabricator Well

- Designed for bottom-mount installation and requires hard wiring
- Beveled edge for easy cleaning
- Thermostatic control
- Deep drawn well is 20-gauge 18-8 stainless steel
- Meets NSF performance standards
- Allows use of full-size and fractional pans up to 6" (15.2 cm) deep while still providing moist heat



ITEM #	WELL*	OVERALL DIMENSIONS IN (CM)	REMOTE CONTROL LEADS IN (CM)	WATTS	VOLTAGE	AMPS
36352	I	14 <sup>3</sup> / <sub>2</sub> X 22 <sup>1</sup> / <sub>2</sub> (35.8 X 56.2)	36 (91.4)	1000	120	8.3
36353	I	14 <sup>3</sup> / <sub>2</sub> X 22 <sup>1</sup> / <sub>2</sub> (35.8 X 56.2)	72 (182.9)	1000	120	8.3
36354	I	14 <sup>3</sup> / <sub>2</sub> X 22 <sup>1</sup> / <sub>2</sub> (35.8 X 56.2)	36 (91.4)	1000	208-240	3.6-4.2
36355	I	14 <sup>3</sup> / <sub>2</sub> X 22 <sup>1</sup> / <sub>2</sub> (35.8 X 56.2)	72 (182.9)	1000	208-240	3.6-4.2
36356	V	14 <sup>3</sup> / <sub>2</sub> X 22 <sup>1</sup> / <sub>2</sub> (35.8 X 56.2)	36 (91.4)	1000	120	8.3
36360	V	14 <sup>3</sup> / <sub>2</sub> X 22 <sup>1</sup> / <sub>2</sub> (35.8 X 56.2)	72 (182.9)	1000	120	8.3
36358	V	14 <sup>3</sup> / <sub>2</sub> X 22 <sup>1</sup> / <sub>2</sub> (35.8 X 56.2)	36 (91.4)	1000	208-240	3.6-4.2
36359	V	14 <sup>3</sup> / <sub>2</sub> X 22 <sup>1</sup> / <sub>2</sub> (35.8 X 56.2)	72 (182.9)	1000	208-240	3.6-4.2

\*I = Industry and V = Vollrath wells    \*\*With 3/8" (2.2 cm) corner radius    Note: Modular Drop-Ins cannot be canceled or returned



Go to [VOLLRATH.com](http://VOLLRATH.com) for presentations about modular drop-in operation, features, and benefits