

TMT-SERIES
as indicated

TMT-FT1



TMT-IO1

AVAILABLE IN
AUGUST 2020

TMT-CDF4



TMT-CDF5



TMT-CDF3



TMT-CDF2



TMT-RF4



TMT-RF3



TMT-RF2



TMT-RF1

FROTHING

- ◆ Includes pot clip
- ◆ Recalibrate for accuracy

ITEM	NSF	TEMPERATURE RANGE	DIAL FACE	PROBE	OC AVAILABLE	UOM	CASE
TMT-FT1		0-220°F -18-104°C	1" Dia	5"L	Optional	Each	12/144

CANDY/DEEP FRYER

- ◆ Includes pot clip

ITEM	NSF	TEMPERATURE RANGE	DIAL FACE	PROBE	GUIDELINE ON DIAL	OTHER FEATURES	UOM	CASE
TMT-CDF2		100-400°F; 40-200°C	2" Dia	5"L	HACCP	• Adjustable Indicator • Recalibratable	Each	12/144
TMT-CDF3		100-400°F; 40-200°C	2" Dia	12"L	HACCP	• Adjustable Indicator • Recalibratable	Each	12/144
TMT-CDF4	N/A	100-400°F; 40-200°C	2" x 11-3/4"	N/A	N/A	• Top Hanging • Vertical Read	Each	12/72
TMT-CDF5		100-500°F; 40-260°C	3" Dia	12"L	HACCP	• Adjustable Indicator • Recalibratable	Each	6/36

REFRIGERATOR/FREEZER

ITEM	NSF	TEMPERATURE RANGE	DIAL FACE	GUIDELINE ON DIAL	MOUNTING	UOM	CASE
TMT-RF1		-26-86°F; -30-30°C	2-7/8" x 5/8"	N/A	Suction Cup Included	Pack	12/144
TMT-RF2		-20-70°F; -30-21°C	2" Dia	HACCP	Built-in Hanging Hook & Standing Panel	Each	12/72
TMT-RF3		-20-70°F; -30-21°C	3" Dia	HACCP	Built-in Hanging Hook & Standing Panel	Each	12/72
TMT-RF4		-20-80°F; -28-26°C	3-1/2" x 1-1/8"	HACCP	Suction Cup Included	Each	12/72

INDOOR / OUTDOOR

- ◆ Weather resistant, rust proof
- ◆ Install with hanging hook or double-sided adhesive (included)

ITEM	NSF	TEMPERATURE RANGE	DIAL FACE	GUIDELINE ON DIAL	MOUNTING	UOM	CASE
TMT-IO1	N/A	-40° - 120°F; -40° - 50°C	1-3/4" Dia	N/A	Built-in Hanging Hook or double-sided adhesive	Each	12/144

