

THERMOMETERS

NSF TMT-SERIES
as indicated



NEW

AVAILABLE IN
AUGUST 2020



TMT-HH1



TMT-P2



TMT-MT2



TMT-P1



TMT-P3



TMT-MT3



TMT-OV2



TMT-OV3



TMT-GS2



TMT-IR1

HOT HOLDING

◆ Hang or stand-alone

| ITEM | NSF | TEMPERATURE RANGE | DIAL FACE | GUIDELINE ON DIAL | UOM | CASE |
|---------|-----|-----------------------------|-----------|-------------------|------|-------|
| TMT-HH1 | | 100° - 180°F; 38° - 82°C | 2" Dia | HACCP | Each | 12/96 |

POCKET TEST

◆ Includes protective sleeve with built-in clip

◆ Recalibrate for accuracy

| ITEM | NSF | TEMPERATURE RANGE | DIAL FACE | PROBE | GUIDELINE ON DIAL | UOM | CASE |
|--------|-----|----------------------------|-----------|-------|-------------------|------|--------|
| TMT-P1 | | 0 - 220°F; -18 - 104°C | 1" Dia | 5"L | HACCP | Each | 12/72 |
| TMT-P2 | | -40 - 180°F; -40 - 80°C | 1" Dia | 5"L | HACCP | Each | 12/72 |
| TMT-P3 | | 50 - 550°F; 10 - 288°C | 1" Dia | 5"L | HACCP | Each | 12/144 |

MEAT

◆ Hand held with adjustable indicator

| ITEM | NSF | TEMPERATURE RANGE | DIAL FACE | PROBE | GUIDELINE ON DIAL | UOM | CASE |
|---------|-----|---------------------------|-----------|-------|-------------------|------|--------|
| TMT-MT2 | | 130 - 190°F; 55 - 85°C | 2" Dia | 5"L | HACCP | Each | 12/144 |
| TMT-MT3 | | 130 - 190°F; 55 - 85°C | 3" Dia | 5"L | HACCP | Each | 12/72 |

OVEN

◆ Hanging hook and standing panel are built-in

| ITEM | NSF | TEMPERATURE RANGE | DIAL FACE | GUIDELINE ON DIAL | UOM | CASE |
|---------|-----|---------------------------|-----------|-------------------|------|--------|
| TMT-OV2 | | 40 - 500°F; 10 - 260°C | 2" Dia | HACCP | Each | 12/144 |
| TMT-OV3 | | 40 - 500°F; 10 - 260°C | 3" Dia | HACCP | Each | 12/144 |

GRILL FACE

◆ Flat surface for grill-top

| ITEM | NSF | TEMPERATURE RANGE | DIAL FACE | GUIDELINE ON DIAL | UOM | CASE |
|---------|-----|----------------------------|-----------|-------------------|------|-------|
| TMT-GS2 | | 150 - 700°F; 70 - 370°C | 2" Dia | HACCP | Each | 3/144 |

INSTANT READ

◆ Includes protective sleeve with built-in clip

◆ Can be calibrated

| ITEM | NSF | TEMPERATURE RANGE | DIAL FACE | PROBE | GUIDELINE ON DIAL | UOM | CASE |
|---------|-----|---------------------------|------------|-------|-------------------|------|-------|
| TMT-IR1 | | 0 - 220°F; -18 - 104°C | 1-3/4" Dia | 5"L | HACCP | Each | 12/72 |