High-performance motor with impact-resistant stainless steel blades adds power and performance to your busy establishment.

68 OZ (2 L) LARGE CAPACITY COMMERCIAL BLENDER

- ♦ 68 oz (2 L), break-resistant and BPA-free Tritan™ container
- High-performance 2 hp motor; unique high-impact blades
- ♦ Metal-to-metal coupling; easy to operate "PULSE" and
- "ON /OFF" paddle controls & variable speed control dial
- Container/pitcher is heat-resistant up to 226°F (108°C); reduce pressure by removing cap in the lid
- Removable container cover and cap for adding/blending ingredients mid-cycle
- 11-1/2" tamper included fits through lid opening and reaches full length of container to blend/stir while mixing
- All parts (except bases & blade fixing block) are dishwasher safe
- One year parts and labor warranty


ļ	OVERALL DIMENSIONS			POWER	PLUG	SHIP
	WIDTH	DEPTH	HEIGHT	TOWER	1 200	WEIGHT
	8-11/16" (220mm)	9-13/16" (249mm)	19-5/16" (490mm)			
	CONTAINER DIMENSIONS			120V~60Hz, 1450W, 12.1A	NEMA 5-15P	10.36 lbs
	WIDTH	DEPTH	HEIGHT	120V~00112, 1400W, 12.1A	TVEIWIX O TOT	(4.7 kgs)
	6-11/16"	6-11/16"	12-3/8"			
l	(178mm)	(178mm)	(314mm)			




44 OZ (1.25 L) 2-SPEED QUIET BAR BLENDER

- 44 oz (1.25 L), break-resistant and BPA-free Tritan™ container
- Quiet, high-performance 1/2 hp self-lubricating motor; uniquely designed high-impact blades
- HIGH/LOW toggle switch for precise consistency control
- Blade is removable for easy cleaning
- Non-skid feet securely grip the surface for stable operation
- Removable container cover and cap for adding/blending ingredients mid-cycle
- One year parts and labor warranty

OVERALL DIMENSIONS			POWER	PLUG	SHIP	
WIDTH	DEPTH	HEIGHT	POWER	PLUG	WEIGHT	
7" (178mm)	7-7/16" (189mm)	15-7/16" (392mm)				
CONTAINER DIMENSIONS			120V~60Hz, 400W, 3.5A	NFMA 5-15P	5.51 lbs	l
WIDTH	DEPTH	HEIGHT	120V~00Hz, 400W, 3.3A	NEWA 3-13F	(2.5 kgs)	l
7"	5-1/8"	9-1/4"				l
(178mm)	(130mm)	(235mm)				ı



ACCELMIX™ BLENDERS





XLB-1000





TRITAN $^{\text{TM}}$ CONTAINER





TRITAN™ CONTAINER





